

HHTAY-50-21 (7/8" s)



Construction		
	Material	Diameter(mm)
Inner Conductor	Helical Corrugated Copper Tube	9.40
Dielectric	Foamed PE	23.0
Outer Conductor	Ring Corrugated Copper Tube	24.9
Jacket	PE or Low Smoke Halogen-free Fire-retardant PE	27.5
Electrical & Mechanical Properties		
Impedance (Ohm)		50±1
Capacitance(pF/m)		76
Velocity(%)		80
Peak Power Rating(kw)		90
RF Peak Voltage (kv)		3.1
Insulation Resistance(M Ω . km)		>5000
Cut-off Frequency(GHz)		4.9
Insulation Voltage(kv)		6
Inner Conductor DC Resistance(Ω /km)		2.9
Outer Conductor DC Resistance(Ω /km)		1.2
Jacket Spark(kv)		8.0
Shielding Effectiveness(dB)		>120
Min. Single Bending Radius(mm)		80
Min. Repeated Bending Radius(mm)		125
No. of Bends		15
Tensile Strength(kg)		102
Storage Temp.(°C)		-55~+85
Installation Temp.(°C)		-40~+60
Operating Temp.(°C)		-55~+85
	Frequency	dB
VSWR ≤ (Return loss ≥ dB)	0.005—3GHz	1.15 (23)
	0.8—1.0GHz	1.10 (26)
	1.7—2.0GHz	1.10 (26)
	2.0—2.4GHz	1.10 (26)

Attenuation (VSWR1.0,cable temp.20℃) and Average Power (VSWR1.0,ambient temp.40℃)

Frequency(MHz)	Attenuation(dB/100m)	Average Power(kw)
100	1.30	6.62
200	1.87	4.60
450	2.85	2.99
800	3.90	2.19
900	4.15	2.06
1000	4.42	1.93
1500	5.53	1.54
1800	6.12	1.39
2000	6.52	1.31
2200	6.90	1.24
2400	7.35	1.19
2500	7.65	1.16
3000	8.25	1.04